## **PENDING CLAIMS**

## Claims 1-6 (Canceled)

- 7. (Rejected) An acoustic projector comprising a single cylindrical shell segment and only two longitudinally spaced drivers mounted within said shell segment.
- 8. (Canceled)
- 9. (Rejected) The acoustic projector defined in claim 7 wherein the shell segment is formed of an epoxy graphite material.
- 10. (Rejected) The acoustic projector defined in claim 7 wherein the combined longitudinal length of the two drivers in the shell segment is between 70% and 90% of the longitudinal length of the shell segment.
- 11. (Rejected) The acoustic projector defined in claim 7 wherein the shell segment is formed with a longitudinal slot.
- 12. (Objected to) The acoustic projector defined in claim 11 wherein arcuate segments of material are mounted within the interior of the shell segment and extend along opposite sides of the slot.
- 13. (Allowed) The acoustic projector defined in claim 17 when the arcuate segments are formed of a dielectric material.
- 14. (Allowed) The acoustic projector defined in claim 17 wherein the drivers are arcuate shaped members and are retained in their respective shell segment by the arcuate shaped segments.

- 15. (Allowed) The acoustic projector defined in claim 17 including a metal liner extending longitudinal along and mounted between the interior of the shell segments and the spaced drivers and electrically insulated from the drivers to provide structural reinforcement to the projector.
- 16. (Rejected) The acoustic projector defined in claim 7 wherein two shell segments are longitudinally joined with each of the shell segments containing two longitudinally spaced drivers.
- 17. (Allowed) An acoustic projector comprising an even number of longitudinally-joined cylindrical shell segments, each of the shell segments being formed with a longitudinal slot; an even number of spaced drivers mounted within each of said shell segments, each of the drivers being in a longitudinal spaced relationship from the adjacent driver; and arcuate segments of material mounted within the interior of the shell segments and extending along opposite sides of the slots.